

DIP **DO IT BY PROFESSIONALS**

APPLICATION GUIDELINE

WATERPROOFING OF **BATHROOM - NEW**

Step:1 Use integral waterproofing compound during construction

As per the guidelines of the manufacturer apply the integral waterproofing compound upto optimum dosage in the concrete and plaster for making waterproof structure.

Product Suggestion:

FAIRCRETE RMW:

Step:2 Surface Preparation for the application of WATERPROOFING OF BATHROOM - NEW

The substrate must be sound, clean, dry, or saturated surface dry (SSD) and free of all contaminants such as oil, grease, coatings, and surface treatments, etc.

Weak concrete must be removed and surface defects such as blow holes and voids must be fully exposed. Repairs to substrate, filling of blow holes/voids and surface leveling must be carried out using fast setting mortars.

Step:3 Priming

Before the application of coating one coat of primer is applied as per guidelines of the manufacturer.

Step:4 Application of WATERPROOFING OF **BATHROOM-NEW**

Apply the product as per guidelines of the manufacturer. Before starting the application check the availability of approximate required material and equipments suggested by the manufacturer.

PRODUCT SUGGESTION

WATERGUARD LIQUID MEMBRANE:

https://bit.ly/3CWzpLZ

WATERGUARD A: https://bit.ly/3AWq19r

Your problem-Our concern



Step:5 Curing

Allow the surface to cure adequately as per guided by manufacturer.

Step:6 Fixing of tiles

Use suitable tile adhesive and tile grouts for preventing future leakages and deterioration of structure.

Step:7 Cleaning

After completion of the application verify the work with customer and clean the entire surface area before leaving the site.

WARRANTY

DIP provides the warranty for the work executed for the application. The following work shall be warranted for **60 month** from the date of completion. DIP gives a repair warranty for the work done and if any further damages what so ever it will not being covered under this. The warranty of DIP will be seized if any natural calamities or it has been damaged intentionally, is tampered, punctured by fasteners in any circumstances. This warranty will only applicable for the work executed by DIP and it will not have any other liabilities in your premises or your structure.

Our product partners



*The information relating to the guidelines of the application are given in good faith based on our current knowledge and experience. In practice, the process may vary depending upon the actual site conditions.

The information given in this document is based on both the current development work and many years of field experience. Whilst every effort is made to ensure that the information is reliable, we cannot accept the responsibility for any work carried out with our materials as we have no control over methods of application, site conditions etc. The user of the product must test the product's suitability for the intended application and purpose. In view of the continuing research and development being undertaken in our laboratories. Fairmate reserves the right to change the properties of its products. We advise customers in their own interest to ensure that this data sheet has not been supersede by a more up-to-date publication. All products are sold subjected to our standard conditions of sale which are available on request. Field services, where provided, does not constitute supervisory responsibility. For additional information, please contact our local FAIRMATE representative. The provided is a supervisory responsibility of the provided information of the provided in the provi











