



DIP

DO IT BY PROFESSIONALS

APPLICATION GUIDELINE

Your problem-Our concern

GROUTING

Step:1 Surface Preparation for the application of GROUTING

All contaminated surfaces must be cleaned thoroughly by chemical or mechanical methods. (2) All bolt pockets and under bases must be free from dust, laitance and of sound substrate. If needed, substrate with water to allow for full absorption for atleast 24 hours. Just before the grouting is to commence, all water must be removed completely leaving the surface only damp.

Step:2 Application of GROUTING

Apply the product as per guidelines of the manufacturer. Before starting the application check the availability of approximate required material and equipments suggested by the manufacturer.

PRODUCT SUGGESTION

FLOWGROUT 60 : <https://bit.ly/3m7qZLQ>

FLOWGROUT EP : <https://bit.ly/37Qcp2L>

Step:3 Curing

Allow the surface to cure adequately suggested by the manufacturer.



Step:4 Cleaning

After completion of the application verify the work with customer and clean the entire surface area before leaving the site.

WARRANTY

DIP provides the warranty for the work executed for the application. The following work shall be warranted for **36 month** from the date of completion. DIP gives a repair warranty for the work done and if any further damages what so ever it will not being covered under this. The warranty of DIP will be seized if any natural calamities or it has been damaged intentionally, is tampered, punctured by fasteners in any circumstances. This warranty will only applicable for the work executed by DIP and it will not have any other liabilities in your premises or your structure.



*The information relating to the guidelines of the application are given in good faith based on our current knowledge and experience. In practice, the process may vary depending upon the actual site conditions.

The information given in this document is based on both the current development work and many years of field experience. Whilst every effort is made to ensure that the information is reliable, we cannot accept the responsibility for any work carried out with our materials as we have no control over methods of application, site conditions etc. The user of the product must test the product's suitability for the intended application and purpose. In view of the continuing research and development being undertaken in our laboratories, Fairmate reserves the right to change the properties of its products. We advise customers in their own interest to ensure that this data sheet has not been superseded by a more up-to-date publication. All products are sold subjected to our standard conditions of sale which are available on request. Field services, where provided, does not constitute supervisory responsibility. For additional information, please contact our local FAIRMATE representative.